

3. Pages

The browsable pages are defined in the "Pages" entity. A page consists of some basic information and a list of components.

Pages + Opret 🔍 Søg 🗑 Nulstil liste visning 📄 Visninger 🔗 Url 📄 Filer 👁 Views 🔔 Logs

	TITLE ▾	PATH ▾	STATUS ▾
✎	Subpage	demo/subpage	Deployed
✎	Demo	demo	Deployed
✎	Welcome		Deployed

Side 1 af 1 ⏪ ⏩ 1 ⏪ ⏩ Poster 3 Sidelængde: 10 20 50 100 500

A page is composed of 8 attributes.

The name

The name shown in the window title.

The path

The url that a user should navigate to, to view this page.

Gets auto-generated based on the title.

Must be unique.

A description

A description for the administrators.

Is not outputted.

A list of components

The actual content of the site.

CSS classes

Classes to add to the body tag.

Can be used to control background/accent colors.

A Wrapper

The wrapper to use for this page.

A Stylesheet

The stylesheet to use for this page.

Cache option

Should the rendered component be cached in memory.

Do not enable this option, if the page contains information about the signed in user.

At the top of the page there is a preview button. Clicking this will clear the cache and open the page, displaying the page as it would be, if navigated to by a user.

Page

Output ▾

Kopier værdier

Indsæt værdier

Slet post

Logs ▾

Marker denne

Preview page

Title

Demo

✓

Path

demo

✓

Description

Components

	SORT ORDER	COMPONENT TYPE	TITLE	CACHE OUTPUT	STATUS
	1	Menu	Menu	Nej	Active
	2	Header 1	Demo side	Ja	Active
	3	Hero Image	Sample image	Ja	Active

Tilføj Components

Classes

Wrapper

Demo

▾

Stylesheet

Demo

▾

Cache output

☐

Status

Deployed

▾

What a page component is composed of, depends on the component type selected. There are 2 required components.

Sort order

Controls the order of the components, when rendering the page.

Component type

The template to use when rendering.

There are a couple different optional components, and this list is not set in stone, it can be adjusted to match the needs of the defined component types.

Multiline text 1-4

Multiline text boxes.

Any new-line will be replace with an html break tag.

Prepending lines with a * will konvert them to an unordered list.

Prepending the entire text with a * will konvert all lines til items in an unordered list.

Image 1-2

Reference to a media file.

Has a preview attached, that updates with the selection.

CSS classes

Classes to add to the component.

Can be used to control background/accent colors.

Cache output

Should the rendered component be cached in memory.

Do not enable this option, if the page contains information about the signed in user.

Page Component

Output ▼Kopier værdierIndsæt værdierSlet postLogs ▼Marker denne

Page	Demo
Sort order	3 ✓
Component type	Hero Image ✓ ▼ 🔗
Classes	
Title	Sample Image ✓
Image 1	127 little bugs in the code ▼ 🔗
	
Cache output	☒
Status	Active ▼

Every time a page is saved, if the path changed, the system will add a redirect from the old path to the current one.

Saving a page or a component that is cached will not result in the cache being cleared.

Revision #3

Created 15 October 2026 08:13:10 by Theis Villumsen

Updated 16 October 2026 08:00:13 by Theis Villumsen