

# Move a File

## What it does

Moves a file from one document-field to another, on the same entity.

Works between document-fields with and without signing.

## How to invoke

Add the following snippet to the entity scripts. This enables movement between all document-fields on the entity.

It adds another column to the file-lists, with a "Move" link. When clicked it opens a popup, with a dropdown where the new field can be selected.

```
const moveFile = (id, to) => {
  const params = new URLSearchParams(window.location.search)
  $.ajax({
    url: "main",
    method: "GET",
    data: {
      "command": "dk.tempusserva.codeunit.common.MoveFile",
      "SagID": params.get("SagID"),
      "DataID": params.get("DataID"),
      "FileID": id.split("_")[2],
      "FieldFrom": id.split("_")[1],
      "FieldTo": to,
    },
  },
  success: (data) => {
    if (data == "File moved") {
      $('##{id}`).find("td").last().html("Moved")
    } else {
```

```

    alert(data)
  }
},
})
}

$(() => {
  const moveFileAction = () => {
    console.log("yay")
    moveFile($("#modeFileFrom").val(), $("#moveFileTo").val())
    $("#moveFilePopup").remove()
  }
  $(() => {
    $(".tableFiles").each((i,e) => {
      let t = $(e)
      t.find("thead").find("tr").each((i,e) => { $(e).append("<th></th>") })
      t.find("tbody").find("tr").each((i,e) => { $(e).append(`<td><a href="#"
class="moveFile">Move</a></td>`) })
    })
    $(".moveFile").on("click", (e) => {
      e.preventDefault()
      let t = $(e.currentTarget)
      let id = t.parent().parent().attr("id")
      let r = `<select class="form-control" id="moveFileTo">`
      r += `<option value="">Select a field</option>`;
      $(".uploadFiles").each((i,e) => {
        let p = $(e).parent().attr("id").replace("VB_DATA_", "")
        if (id.split("_")[1] != p) {
          let x = $(e).parent().parent().parent().find(`#NB_DATA_${p}`).html()
          r += `<option value="${p}">${x}</option>`
        }
      })
      r += "</select>"
      $("#TempusServaPage").append(`
<div id="moveFilePopup" style="display: none;">
  <label>Move file to:</label>
  ${r}
  <input type="hidden" id="modeFileFrom" value="${id}">
  <a href="javascript:moveFileAction();" class="moveFileAction">Move</a>

```

```
</div>
`
createJqueryDialog("moveFilePopup")
})
})
})
```

# Configuration

None

# Developer info

- Type: [CodeunitPagecontent](#) (raw)
- Security: Requires session
- Classpath: dk.tempusserva.codeunit.common.MoveFile

---

Revision #1

Created 4 April 2025 12:20:20 by Theis Villumsen

Updated 4 April 2025 12:23:29 by Theis Villumsen