

# Toggling fields (5478+)

Note: Hide functions are NOT intended for denying access to data -it will only be hidden in the frontend, but is still accessible to savvy users.

Fields can be shown or hidden calling the fieldname

- **hideField(fieldName)**
- **showField(fieldName)**

Examples

```
hideField("USER");  
hideField("StatusID");
```

## Dependent toggling

Hiding and showing fields can be made dependent on classes in the TempusServaPage

- **hideFieldForPageClass(fieldName,className)**
- **showFieldForPageClass(fieldName,className)**

Hiding and showing fields can be made dependent on items current status.

- **hideFieldForStatusId(fieldName,statusId)**
- **showFieldForStatusId(fieldName,statusId)**

Hiding and showing fields can be made dependent on classes in the TempusServaPage AND items current status.

- **hideFieldForPageClassAndStatusId(fieldName,className,statusId)**
- **showFieldForPageClassAndStatusId(fieldName,className,statusId)**

In case of advanced setup consider "hide for all first and show for some later". In this example NAME should only be displayed for a few status

```
hideField("NAME");  
showFieldForStatusId("NAME",1234);  
showFieldForStatusId("NAME",1235);
```

# Disclaimer

The functions are the equivalent of JQuery

```
$("#VB_DATA_"+fieldName).parent().parent().hide();  
$("#VB_DATA_"+fieldName).parent().parent().hide();
```

This means that fields are expected to be wrapped in TWO layers of html tags for the functions to work

---

Revision #2

Created 25 March 2025 15:01:46 by Theis Villumsen

Updated 21 July 2025 10:25:46 by Theis Villumsen