

Policy reference

Documentation for shared server configuration options

- [Server configuration](#)
- [Interface behaviour](#)
- [Active directory](#)
- [Security](#)
- [Scheduled services](#)
- [Debug](#)
- [Filesystem](#)
- [Service daemon](#)
- [Mail server](#)
- [Remote services](#)
- [Protection](#)
- [License](#)
- [SMS service](#)
- [Database](#)
- [Main menu](#)
- [Special fields](#)
- [Designer](#)
- [Layout](#)
- [Rendering](#)
- [Staging](#)
- [Codeunit](#)
- [Language / I18N](#)
- [OLAP cubes](#)
- [REST webservice](#)
- [Password policy](#)
- [Statistics](#)
- [Satelite server handling](#)

- [FTP server](#)
- [Menu customization](#)
- [WebDAV](#)
- [Single Sign On](#)

Server configuration

System name	Display name	Explanation	Extra info
applicationBasePath	Application folder	Location of WAR / deployed web application	
applicationDisplayName	Application display name	Name of application displayed to users	
applicationPort	Server port for HTTP	Port used for running regular requests. Needs to match the setting in the webcontainer definition (server.xml in Tomcat)	
applicationPortSSL	Server port for HTTPS	Port used for running SSL encrypted requests. Needs to match the setting in the webcontainer definition (server.xml in Tomcat)	
applicationName	Application name	Name of application / folder - example http://myserver.com/APPLICATIONNAME/login	
applicationServer	Application server hostname or IP	Base reference for the server. IP example: 89.56.12.14. Network name: localhost. Domain: bpms.acme.com	
applicationURL	Application machine / URL	Base URL of the server as seen by the end user. Overlaps with value in applicationServer	
cacheActive	Caching enabled (recommended)	Enable caching of system resources. Alternative: Collect all resources every time (very slow)	
cacheBrowserExpiresSeconds	Static content cache time (seconds)	Amount of time that images and scripts are cached in client browser.	
cacheMaxObjectSize	Cache maximum size (bytes)	Maximum amount of memory consumed by the cache. Set as high as possible.	

connectionPoolActive	Use connection pools (recommended)	Strongly recommended. Use webcontainer connection pools. Alternative: Application builds own connections (very slow)	
defaultCharEncoding	Default Character Encoding	Recommended: ISO-8859	
doExtraUrlDecoding	Decode autocompletion / quicksearch	Use if experiencing problems with autocompletion / quicksearch	
doRedirectAfterUpdate	Redirect user after updates	Strongly recommended. Slight performance hit, but enables browser BACK button	
multiServerCoordination	Server cluster coordination	Coordinate cache flushing, user list etc. through database communication (polling).	
serverTypeAutodetect	Server type detection	Autodetect compliance type	
serverTypeJ2EE	Server type J2EE	Compliance type if autodetect is disabled	
sessionCheckInterval	Session cleanup interval (minutes)	Time between online list sweeping, removing user with no recent activity.	
sessionLifetimeMaximum	Session lifetime (minutes)	Maximum time since last activity before users must log in again	
sessionLifetimeMinutes	Session lifetime minutes	Length of user sessions (changeable at runtime)	
systemOptimizeMemory	Minimize HEAP size	Always recommended < 1Gb RAM. Tradeoff between RAM and CPU time	

Interface behaviour

System name	Display name	Explanation	Extra info
allowAliasQueryParameters	Allow Query alias parameters	Allow alternate names for parameters used in LIST searches. Alternate names can be set programmatically.	
allowFieldSelectionInLists	Allow field selection in lists	Allow user to select which fields are displayed in LIST views	
allowListQuickFilter	Allow for Quick filters i list views	Enable search in lists by writing part of the name (a search box will appear)	
allowListSubtableRendering	Data subtables in lists	Subtables can negatively affect performance	
allowSubtableLists	Allow subtables in items (recommended)	Allow related child records to be displayed in ITEM level views	
concurrencyWarnings	Warn on simultaneous item editing	Users poll server for changes using AJAX in browser client (some performance impact). Note that only different users editing the same item will trigger a warning.	
defaultLanguageID	Default Language (ID)	Language to use if nothing else is specified and autodetection is disabled. Test by adding &Language=[number] to URL	
defaultStyleID	Default Style (ID)	Style (buttons) to use if nothing else is specified. Test by adding &Style=[number] to URL	
defaultStylesheetID	Default Stylesheet (ID)	Stylesheet to use if nothing else is specified. Test by adding &Stylesheet=[number] to URL	

defaultTemplateID	Default Template (ID)	Form template to use in ITEM mode if nothing else is specified. Test by adding &Template=[number] to URL	
defaultWrapperID	Default Wrapper (ID)	WrapperID to use if nothing else is specified. Test by adding &Wrapper=[number] to URL	
doFormAutosave	Autosave changed forms	Allow editor to autocommit data before session times out	
doItemBrowserTitle	Display item resume in browser title	Change browser title/tab title to current records Resume value in ITEM mode	
doItemCreateAddMore	Button to add more records	Add multiple records during new record creation (button)	
doItemMenuCopyPaste	Show copy/paste in during record edits	Extra buttons for copy/paste operations in ITEM mode	
DoLinkedCSS	CSS style links	Link CSS content so that browsers can cache the content. Recommended.	
doListShowAllFields	Allow show all fields button	Optional button i menu for selecting all columns / fields in LIST mode	
doListShowAllRecords	Allow show all records in list view	Optional button i menu for selecting all records in LIST mode	
doListShowLinkHeader	Display link in headers	Display link to list as part of header name	
doListShowNameHeader	Display header in lists	Display the name of the solution above the list	
doListShowSearchHeader	Show search headers	Display descriptive header in search form	
doPageNavigatorAllways	Always show navigator in lists	Page navigator can be disabled if all records can displayed in one page	
doPersonalFlagsOnItems	Display user flags on items	Allow users to make bookmark / personal comments on single items	

doPersonalLinksOnItems	Display personal links on single items	Display submenu of personal options in ITEM mode. By default only displayed i list / main mode	
doPersonalLinksOnLists	Display personal links on lists	Display submenu of personal options in LIST mode.	
doRecentItemsBookmarks	Show recent items list	Track and display recently accessed items.	
doStatusFinalDisableEditing	Disable editing if status is final	Allow records to be edited even after the item has reached a status that is final	
DoTimeDecimal	Display date sums with decimals	Is time measured on items displayed using decimal and integer values	
errorAdvancedView	Advanced error handling	Display explanation and contact details if exceptions occur	
errorUnkownImage	Advanced error logo	Logo to display in advanced error handling	
guiClickableList	Click/doubleclick lists	List views can be clicked to edit (double) or show (single)	
guiDialogAdvanced	Use advanced popups	Uses JQuery style dialog for poup windows with inline scrolling	http://jqueryui.com/dialog/
guiFieldHelpOffsetLeft	Field help popup offset LEFT	Window relative position to link on X axis	
guiFieldHelpOffsetTop	Field help popup offset TOP	Window relative position to link on Y axis	
guiPreventDoubleClick	Prevent doubleclick	Deactivate multi click on codeunit buttons	
guiSetFormFocus	Set form focus	Set focus to first element in edit mode	
guiSmartKeystrokes	Use keyboard navigation	Navigate with arrow keys, escape and tabulation	Features/Key navigation
guiTouchEnhancement	Enhance touch experience	Make larger buttons and enable quicksearch by default	
headerSeperator	Separator sign for headers	Dot between header parts - ex. MySolution - Dashboard	
mainRedirect	Main menu redirect active	Redirect to alternative main menu active	

mainRedirectUrl	Main menu redirect URL	Local path ex. main?command=list&SagID=0	
renderMenuItemClass	Use CSS class for menu items	Give unique class property to each menu item.	
subformLinesDefault	Number of lines in subforms	Default number of records displayed in subforms	
toolBarcodeParameters	Barcode additional parameters	Extra parameter for barcode, for tweaking size, type etc.	
userOnlineList	Maintain list of online users	Monitor users online - ie. users with an active session on the server. Recommended in single front server environments.	
userRequireAcceptTerms	Require new user to accept usage terms	Configure text in System configurations	

Active directory

System name	Display name	Explanation	Extra info
IdapAuthentication	Use LDAP authentication	Is LDAP logon active ?	Integration/LDAP
IdapAuthenticationFallback	Use fallback authentication if LDAP fails	Allow internal database verification using stored passwords, in the event that the LDAP server fails to respond properly.	Integration/LDAP
IdapCreateUsers	Allow creation of new users	Create users logging in, that cannot be found inside the LDAP. User must belong to IdapDomainDefault	Integration/LDAP
IdapDomainDefault	Default domain		Integration/LDAP
IdapMaintainGroupsOnLogon	Maintain groups on logon	LDAP validation also synchronizes groups found for logged in user.	Integration/LDAP
IdapServer	LDAP setup: LDAP server	Use IP or network name	Integration/LDAP
IdapUsername	LDAP setup: USERNAME	Service account username. User needs only read access.	Integration/LDAP
IdapPassword	LDAP setup: PASSWORD	Service account username. Note this password is stored cleartext.	Integration/LDAP

Security

System name	Display name	Explanation	Extra info
doAdvancedGroupSecurity	Advanced group security	Enables: A) Groups inside groups B) Multiple exclusive groups	
policyHideValues	Hide overloaded policies	Hide values for policies that have been overloaded in the application deployment file	
securityAllowPublicCodeunits	Allow anonymous codeunit execution	It is considered safe to use special codeunits	
securityEnforceExclusiveGroup	Require normal users to have Exclusive groups	All users except Admins must have at least 1 exclusive group	
securityLoginFailedAttempts	Login max failed logins	Number of failed logins before accounts will be disabled	
securityLoginFailedAutoReset	AutoReset users	Automatically reset users that have failed maximum number of logins (sends new password)	
securityPasswordAcceptMD5digest	Allow MD5 hashed passwords	Recommended in transition between MD5 (minor flaws) and SHA256 (very secure)	
securityPasswordCleartext	Store passwords cleartext	Allow passwords to be stored without one-way encryption	
securityPasswordCleartextAllowed	Allow cleartext passwords	Optionally encode all password using admin services	
securityResetPasswordWithoutLogin	Reset password without login		
securitySslLogin	SSL encryption for login page	Enforce usage of SSL connections on login page using internal redirect. Recommended.	Setting up SSL/HTTPS
securitySslPages	SSL encryption for ALL pages	Enforce usage of SSL connections on all page using internal redirect. Not recommended.	Setting up SSL/HTTPS

securityTokenExpiryEnforce	Deny old style access tokens		
ssoSpnegoAuthenticate	SSO via domain controller	Allow SPNEGO filter to automatically log in authenticated Windows users	
ssoCryptoTokenActive	SSO token authentication	Allow single sign in from external components (ex. TS SSO webpart)	
ssoCryptoTokenSecret	SSO token shared secret	Shared secret password between TS and external services. Value must match exactly.	

Scheduled services

System name	Display name	Explanation	Extra info
accountAnonymousMeasure	Anonymous account (UserID)	UserID used for normal system interactions using the solution interfaces	
adminWarningSmsList	Warning SMS number list	List of administrator mobile phone lists (for notifications)	
healthMonitorPassword	Health monitor password	Parameter/password to access basic monitor service without a login (usage: service?healthMonitorPassword)	
integrationInvokeCodeunit	Integration execute codeunit	Execute codeunits during dataintegration / webservices	
maintenanceEmergencyDelay	Emergency shutdown delay	Number of minutes to warn users when a EMERGENCY signal is sent to the server from the admin services	
maintenanceLockdoorDelay	Maintenance disable login delay	Number of minutes before a shutdown where users are no longer allowed to login	
maintenanceShutdownDelay	Maintenance shutdown delay	Number of minutes to warn users when a MAINTENANCE signal is sent to the server from the admin services	
measureAnonymous	Measure anonymous users		
measureInsertDelayCount	Measure insert delay (items)		
measureInsertDelayMinutes	Measure insert delay (minutes)		
measureInsertUsingBatch	Measure insert in batches		
serviceAdminStatusEmail	Administrator email	Administrator email for sending status updates	

serviceStatusActionSend Directly	Send status actions directly by mail	False: Insert into user notifications. True: Send per email	
serviceWebsiteMonitorG W	Website monitor goodword	Information that needs to be found in a page located at serviceWebsiteMonitorURL	
serviceWebsiteMonitorU RL	Website monitor URL	Address to monitor where the serviceWebsiteMonitorGW should be found	
userOnlineAlertOnNewN otification	Notify online users directly	Display new button when users are already logged in	
userOnlineListDisplayCo unt	Display number of online users	Display number of online users at bottom of all pages	

Debug

System name	Display name	Explanation	Extra info
debugCacheResponse	Caching success / failure	Log effects of caching.	
debugDaemonActivity	Debug daemon runs	Log all runs for Service and Server daemon	
debugDataLoads	Debug while loading data (CSV/XML)	Debugging option for designers and developers	
debugExceptions	Debug all Exceptions	Writes stacktrace to logfiles. Alternative: Only write to eventlog.	
debugIntegration	Debug integration messages	Debugging option for designers and developers	
debugLdapCommunication	Debug LDAP communication	Debugging option for designers and developers	
debugLdapStacktrace	Debug LDAP error details	Debugging option for designers and developers	
debugLdapValidation	Debug LDAP validation	Debugging option for designers and developers	
debugLoginResults	Debug all user logins	Debugging option for designers and developers	
debugOlapDefinitions	Debug OLAP definitions	Write all schemas and queries to logfiles on boot	
debugQuerySQL	Debug all SQL queries	All queries are written to System.out / logfile	
debugQuestionnaire	Debug questionnaire steps	Display extra information in questionnaire mode	
debugRequestPerSecond	Debug requests/second	Calculate server load on run. Results are sent to System.out / logfile	
debugRequestTime	Debug response time		
debugRequestTimeToPage	Debug response time on page	Display response time in bottom of all pages (no performance impact).	
debugScriptFunctions	Debug JavaScript	Allow JS errors to be displayed	
debugServiceDaemon	Debug the Service runner Daemon	Write extra information from service clients to log files	

debugTemplateHandling	Debug template parsing	Debugging option for designers and developers	
debugTokenEvaluation	Debug token evaluation	Debugging option for designers and developers	
debugWebservices	Debug the Webservice interface	Debugging option for designers and developers	

Filesystem

System name	Display name	Explanation	Extra info
folderImportFile	Folder: Import files	Processing folder. Will be set to default value if left empty.	
folderIntegrationCSV	Folder: CSV data files	Processing folder. Will be set to default value if left empty.	<u>CSV file import</u>
folderIntegrationMail	Folder: Mail integration (temporary)	Processing folder. Will be set to default value if left empty.	
folderIntegrationXML	Folder: XML integration processing	Processing folder. Will be set to default value if left empty.	<u>Parsing XML data files</u>
folderTemplateLoad	Folder: Template cache	Processing folder. Will be set to default value if left empty.	
folderTemplateSave	Folder: Template processing	Processing folder. Will be set to default value if left empty.	
folderUpload	Folder: Upload	Will be set to default value if left empty.	
folderUploadTemp	Folder: Upload processing	Processing folder. Will be set to default value if left empty.	
mediaFilterDelayMS	Media files download latency	Use if filesystem is slow to pick up changes	
overloadApplicationFolder	Application folder	Option to override. Empty value = autodetect	
uploadPictureResize	Reduce uploaded pictures	Resize all pictures sent to server to size defined in uploadPictureSizeMaximum	
uploadPictureSizeMaximum	Picture maximum size	Scale pictures to this maximum of pixels. Maximum height/width determines size. Only works if uploadPictureResize is set	
uploadPictureSizeThumbnail	Thumbnail maximum size		

uploadClientScaling	Use clientside graphic scaling	Let browser resize pictures before upload	
uploadClientScalingExclude	Clientside exclusion test for scaling	Set to "false" or exclusion pattern: /Android(?!.*Chrome) Opera/	<u>[1]</u> .test(window.navigator
uploadThreadProcessing	Upload processing threads	Beta function. Handle file processing with threads to improve UI responsiveness.	
uploadThreadOnlyPictures	Upload processing threads: Graphics only	Restrict upload threads to resizable graphics. Requires Upload processing threads	

Service daemon

System name	Display name	Explanation	Extra info
serviceAutostart	Autostart service daemon	Start the service daemon after boot.	
serviceDaemonHeartbeatSeconds	Run daemon every seconds	Frequency of daemon runs. Value should match the frequency of the most demanding service.	
serviceLogentriesConsolidate	Compress logs		
serviceLogentriesMaximumAge	Maximum age logs		
serviceNotificationDeleteAfterDays	Maximum age notifications		

Mail server

System name	Display name	Explanation	Extra info
mailDomain	POP3: Domain		
mailPassword	POP3: Password	Mail account password. Note this password is stored cleartext.	
mailServer	POP3: Server		
mailUsername	POP3: Username	Mail account username.	
smtpMailDelaySec	SMTP: Message delay	Delay in SECONDS between sending emails	Sending emails
smtpPassword	SMTP: Account password	Password for SMTP account set in smtpUsername. Note this password is stored cleartext.	Sending emails
smtpSendRetries	SMTP: Number of retries	Number of attempts to send email from queue before giving up	Sending emails
smtpServer	SMTP: Server address	Network location of the SMTP server	Sending emails
smtpSystemEmail	SMTP: System mail address	Sender address (from) set on all automatically generated emails.	Sending emails
smtpTestEmail	SMTP: Test email address	Recipient of all mails when test mode is activated. Activate by enabling smtpTestMode	Sending emails
smtpTestMode	SMTP: Test mode (send to test email)	Enable test mode where ALL emails are sent to address specified in smtpTestEmail	Sending emails
smtpUsername	SMTP: Account name	Example: k.pedersen@lsvgroup.com	Sending emails

Remote services

System name	Display name	Explanation	Extra info
doLookupEnabledLinks	Allow lookup links for fields		
lookupServiceCvrRegisterUrl	URL to lookup CVR		
lookupServiceGeneral	URL to lookup text		
lookupServicePhonePersonUrl	URL to lookup contacts		

Protection

System name	Display name	Explanation	Extra info
bruteforceCooldownMinutes	Bruteforce reject logins (minutes)	Time that logins are rejected after the bruteforce protection is activated.	<u>Security/Bruteforce</u>
bruteforceMaxBadLogins	Bruteforce maximum failed logins	Amount of logins failed before new logins are rejected. Relative to bruteforceMeasurePeriod.	<u>Security/Bruteforce</u>
bruteforceMeasurePeriod	Bruteforce measure period (minutes)	Timeframe for measuring amount of bad logins. Relative to bruteforceMaxBadLogins.	<u>Security/Bruteforce</u>
bruteforceProtection	Bruteforce detection active	Enable brute force detection mechanisms	<u>Security/Bruteforce</u>
securitySanitizeAllUserInput	Check all user input for JS scripts	Allow only if session variable protection is enabled	

License

System name	Display name	Explanation	Extra info
licenseHolder	License: Owner	Company/institution name on the license	
licenseNumber	License: Number	ID received from your Tempus Serva distributor	
licenseReportAdministrator	2nd recipient of license reports	Secondary recipient of license reporting. Normally the license seller.	
licenseReportingEmail	1st recipient of license reports	Primary recipient of license reporting. Normally the responsible CIO.	
licenseReportLicenseServer	License reporting active	License reporting active	
licenseSerial	License: Serial code	Code received from your Tempus Serva distributor	

SMS service

System name	Display name	Explanation	Extra info
smsConnectUrl	SMS Service gateway URL		
smsErrorMessage	SMS error message		
smsMaxLength	SMS maximum message length		
smsParamMessage	SMS parameter name: Message		
smsParamNumber	SMS parameter name: Number		
smsPhoneCountryCode	SMS phonenumber prefix		
smsPhoneMinLength	SMS phonenumber min length		
smsTestMode	SMS testmode active		Email server setup
smsTestNumber	SMS testmode number		Email server setup

Database

System name	Display name	Explanation	Extra info
dbAutoUpdate	Update database on boot (recommended)	Strongly recommended. Allows system to update the database when new builds are deployed.	
dbNameBase	SHARED database name	Schema name of database with common settings. Database can be shared between multiple installations.	

Main menu

System name	Display name	Explantion	Extra info
doInformationInMasterMenu	Allow news articles	Display relevant news articles and messages on main page	
doMainMenuAccordion	Use animated main menu	Use slick JQuery dropdown accordion based on sections	http://jqueryui.com/accordion/
doMainMenuCreateItems	Display create link in main menu	Display button to create records directly from the mail menu	
doMainMenuDescription	Display descriptions in main menu	Display solution description in the main menu. Alternatively you can just leave the description empty.	
doMainMenuRecentItems	Display recent items in main menu	Display list of recent items accessed for each solution in the list.	
doMainMenuSections	Divide menu into solution groups	Split the main menu into sections.	
doViewListInMasterMenu	Show user views in master menu	Display list of shared and personal views in the main menu	

Special fields

System name	Display name	Explanation	Extra info
allowMultilookupInLists	Allow multilookup in list views	Minor performance impact	
allowRecursiveDelete	Allow recursive record deletion	Allow deletion of parent items to propagate (configure each solution)	
allowRelationDuringCreation	Create related records before save	Allow users to create new child records before the parent is submitted / created.	
doSmartDateInput	Smart date input		<u>Date</u>
lookupCheckKeysAlways	Lookup always check key values		
lookupIgnoreErrors	Lookup ignore errors		
lookupIgnoreErrorsAjax	Lookup ignore AJAX errors		
lookupRecordSingleItemChange	Display 1 record in lookup list changes	Lookup list elements will only display 1 reference after being set the first time	
medicoCloakPersonUniqueId	Cloak person identification data (ex. CPR)	Partially hide sensitive information when not in ITEM edit mode. Example 112233-4455 becomes 112233-XXXX.	
questionnaireAutostart	Questionnaire autostart	Make sure the user cannot navigate to anything else that the first question	
questionnaireLastButton	Last button in questionnaires	Display a button to navigate to questionnaires final page	
questionnaireLastResume	Questionnaire missing field summary	Display missing fields on final page	
questionnaireProgress	Questionnaire progress	Turns progress indication (bar/percentage/steps) on and off	
questionnaireProgressIcons	Questionnaire progress: Bar	Display blue/grey arrows based on progress	

questionnaireProgressPer cent	Questionnaire progress: Percentage	Calculate the completion rate based on progress	
questionnaireProgressSteps	Questionnaire progress: Steps	Display number of completed and leftover questions	

Designer

System name	Display name	Explanation	Extra info
deletionBackup	Deletion backups	Perform backups before deleting solutions / fields	
deletionBackupDefinition	Deletion copy definition	Copy metadata of solution before deletion	
deletionBackupRecordLimit	Deletion backup record limit	Maximum number of records before tables are backup up before deletion	
designerDisplayHelp	Display help section in designer (this menu)		

Layout

System name	Display name	Explanation	Extra info
cssStylesheetBasic	Include Basic stylesheet	Disable if you want 100% style control	
cssStylesheetjQuery	Include JQuery stylesheet	Disable if you want 100% style control	
diagramLargeHeight	Diagram height large	Ex. Runchart details	
diagramLargeWidth	Diagram width large	Ex. Runchart details	
diagramSmallHeight	Diagram height small	Ex. Runchart overview	
diagramSmallWidth	Diagram width small	Ex. Runchart overview	
renderListGroupColumns	Use grouping columns	Group column i moved to the first in the list	
renderListGroupHeaders	Use grouping headers	Alternative: Group values displayed as column	
renderListSortColumns	Use sorting columns	Sort column i moved to the first in the list	
standardHeightMemo	Standard textarea Height	Default height of TEXTAREA. Value can be overloaded in each field configuration.	
standardTextCropLength	Text default crop length		
standardWidthHeader	Header standard width		
standardWidthMemo	Standard textarea Width	Default width of TEXTAREA. Value can be overloaded in each field configuration.	
standardWidthText	Standard inputbox size	Standard INPUT field size. Value can be overloaded in each field configuration.	
windowDefaultHeight	New window height (pixels)	Standard height for IFRAME and popup windows	
windowDefaultWidth	New window width (pixels)	Standard width for IFRAME and popup windows	

Rendering

System name	Display name	Explanation	Extra info
defaultHtmlDoctype	HTML DOCTYPE	First line of HTML response. Change if you need specific HTML compliance. System is natively xhtml 1.0 compliant.	
defaultHtmlEncoding	General encoding for server	Codepage displayed inside the html tag	
defaultHtmlVersion	HTML version number	Version information displayed inside the html tag	
doIncludejQuery	Include JQuery library	Include JQuery in compatibility mode	
doPageSelectViaJquery	Page selectors via JQuery	Use JS components for page selectors (default: static html)	
doIncludeScriptUserInfo	Insert user info JS variables	Inject user information in pages for use with custom JavaScripts	
heatmapCellColorIcon	Heatmap cell icon	Special content inserted into all heatmap cells	Moved to buttons/style in version 8945
heatmapInvertAxis	Heatmap invert axis	Display variables on Y axis and records on X axis	
heatmapItemLinks	Heatmap links to items	Allow direct links from heatmap records	
heatmapLegendMap	Heatmap legend	Display legend map of full variable names	
pageselectorTableLayout	Pageselector in tables	Render pageselectors as tables (normal = div)	
renderLinksCompliant	Render links HTML 4.0 compliant	Encode links to satisfy HTML4 specification	
useGoogleChart	Technology diagram: Google	Alternative use ChartJS (not recommended any more)	
useNewChart	Beta: Use new chart implementation		<u>Dashboard diagram widget configuration</u>

diagramChartJSColors	Colors for charts	Set the colors used by ChartJS	<u>Dashboard diagram widget configuration</u>
showPercentageAsBar	Beta: Show Field-Percent as a progress-bar in lists	If true: Renders percentage fields as bars in list views	<u>Percentage field</u>
useScriptulous	Technology script: Scriptulous	Alternative use JQuery (recommended)	

Staging

System name	Display name	Explanation	Extra info
buildTestLinesDefault	Build test data default size	Amount of lines copied from live system when building sets of test data	
testSessionBackground	Testsession use background	Markup when in test mode:. Set background image with this URL.	
testSessionInlineText	Testsession page information	Markup when in test mode:. Put extra HTML specified in page.	
testSessionTitleChange	Testsession use title	Markup when in test mode:. Set browser title to this text.	

Codeunit

System name	Display name	Explanation	Extra info
codeunitLoadExternal	Load external codeunits	Allow server to load JAR files outside webapplication WEB-INF folder	
codeunitPathJarFile	Filesystem folder for codeunits	Folder that is considered safe to use for built-in class loader	
codeunitPathJarLink	Http URL folder for codeunits	URL that is considered safe to use for built-in class loader	
safeCreateAddGroup1	Fullauto: Add group A	Option for full auto user/exclusivegroup creation	
safeCreateAddGroup2	Fullauto: Add group B	Option for full auto user/exclusivegroup creation	
safeCreateIsDataHandler	Fullauto: Assign DataHandler role	Option for full auto user/exclusivegroup creation	
safeCreateIsUserCreator	Fullauto: Assign UserCreator role	Option for full auto user/exclusivegroup creation	
codeunitLoadPathJarFile	Load all jar files in the folder	Overwrites codeunitLoadLibraryFile	
codeunitLoadLibraryFile	Load only the specified jar files	Based on codeunitLibraryFileList	
codeunitValidateExternal	Enable sha256 validation of external jar files	Only load jar files with hashes found in codeunitExternalHashes (Added in version 11508)	
codeunitExternalHashes	List of trusted sha256 of jar files	List of sha256 hashes of files to be loaded, separated by space, comma or semicolon (Added in version 11508)	

Language / I18N

System name	Display name	Explanation	Extra info
languageGetFromBrowser	Determine language from browser	Pick up language settings from the browsers settings	
languageUseI18N	Use Internationalization	Allow solutions to take advantage of I18N. Configure each solution separately.	

OLAP cubes

System name	Display name	Explanation	Extra info
olapDateDimensionYearEnd	OLAP Time dimension last year		
olapDateDimensionYearStart	OLAP Time dimension first year		
olapEngineFolderURL	OLAP engine URL (optional)		
olapRebuildOnBoot	Rebuild OLAP on boot	Rewrite cube definitions and queries	
olapUseSingleSignon	OLAP Single Sign On	Allow external users with security tokens (set OLAP folder to use dedicated server)	
allowRemoteOlapSchema	OLAP schema service	Activate schema delivery service (remote OLAP servers)	
olapSchemaPassword	OLAP schema service password	Experimental: Password for use with the schema delivery service (remote OLAP servers)	
olapJPivotEnabled	JPivot OLAP enabled	Is the internal OLAP engine enabled (JPivot)	
olapJpivotIncludeDefaultCubes	Jpivot schema include default cubes	Include autogenerated cubes with generated permissions	
olapSaikuEnabled	Saiku OLAP enabled	Experimental: Is the external OLAP engine enabled (saiku)	
olapSaikuIncludeCustomCubes	Saiku schema include custom cubes	Include custom cubes with default permissions	
olapSaikuSettingWebapp	Optional saiku web application name	Default if value is left empty: <current webapp name> + "Saiku"	Example: /SaikuWebapp
olapSaikuSettingServerUrl	Optional saiku server URL	Default if value is left empty: <same server>	Example: http://myserver.com

REST webservice

System name	Display name	Explanation	Extra info
restActive	REST is activated	Option: Disable in web.xml	
restAllowAnonoumous	Anonymous REST sessions	Webuser can interact if given permission	
restAllowAnonoumousSchema	Anonymous REST metadata	Webuser can interact if given permission	
restBasicAuthentication	REST basic authentication	Add Basic authentication	
restListPageSize	REST list service page length	Maximum number of items displayed in a search	
restStrongTypeRequest	Strong types REST requests	Use strong types in WADL	
restStrongTypeResponse	Strong types REST response	Use strong types in XSD	

Password policy

System name	Display name	Explanation	Extra info
passwordExpiry	Password Expiry	Allow passwords to expire according to value set in passwordExpiryAge	
passwordExpiryAge	Password Expiry age	Maximum age of passwords	
passwordExpiryWarning	Days to warn for password expiry	Days to start warning the user about their password expiring, as defined by passwordExpiryAge	
passwordReqCheckOnLogon	Password check rules OnLogon	Enforce password rules on all logons	
passwordRequireLength	Password require length	Minimum total length of password	
passwordRequireLowercase	Password require Lowercase	Content rule lowercase letters (ex. abc)	
passwordRequirements	Password requirements	Enforce password rules	
passwordRequireNumbers	Password require Numbers	Content rule numbers (ex. 123)	
passwordRequireSpecial	Password require Special	Content rule special characters (ex. !#%&)	
passwordRequireUppercase	Password require Uppercase	Content rule uppercase letters (ex. ABC)	

Statistics

System name	Display name	Explanation	Extra info
statisticsRegressionInfo	Extra regression info	Display advanced regression correlation information	
statisticsTargetPValue	Target p-value for tests	At what p-values are tests considered significant	

Satellite server handling

System name	Display name	Explanation	Extra info
serverSateliteMaster	Master: Server is MASTER	The master server controls the satellite, and contains ALL data	
sateliteDatabaseHost	Master: Satellite DB hostname	Connection information for satellite database (requires R/W access)	
sateliteDatabaseJDBC	Master: Satellite DB database	Connection information for satellite database (requires R/W access)	
sateliteDatabaseUser	Master: Satellite DB username	Connection information for satellite database (requires R/W access)	
sateliteDatabasePass	Master: Satellite DB password	Connection information for satellite database (requires R/W access)	
serverSateliteSlave	Satellite: Server is SATELITE	Warning: The satellite is controlled by the master server, and contains a SUBSET of data	
allowRemoteCacheReset	Satellite: Cache reset allowed via URL	Allow anonymous cache reset using only password	
cacheResetNowPassword	Satellite: Cache reset password	Password to include in the URL for the cache reset	

FTP server

System name	Display name	Explanation	Extra info
ftpDbConnection	CrushFTP database Connection	Connection string for CrushFTP authorization database. Example: <i>jdbc:mysql://127.0.0.1/crushftp</i>	
ftpDbUsername	CrushFTP database Username	Username CrushFTP database	
ftpDbPassword	CrushFTP database Password	Password CrushFTP database	
ftpServerPortFtp	CrushFTP port for FTP	Default 21	
ftpServerPortHttp	CrushFTP port for HTTP	Default 8081 for side by side installation	

Menu customization

System name	Display name	Explanation	Extra info
menuLayoutDefault	Menu default layout name	Choose between: layoutClassic layoutRibbon layoutBlockLeft layoutBlockRight	
menuLayoutSelector	Allow user to select menu layout	Layout position selectors will displayed in the main menu	
menuLevelAdvancedDefault	Menu default advanced	Display all menu items by default	
menuLevelSelector	Allow user to select menu level	Simple / advanced selectors will displayed in the main menu	

WebDAV

System name	Display name	Explanation	Extra info
webdavMapDriveInMenu	Map drive button	Add map network drive button in main menu	
webdavSessionLifetime	Session token lifetime	Age before session tokens expire	
webdavSessionTokens	Session token	Session tokens allows direct editing from UI with doing authentication again	
webdavSessionTokensRevalidate	Session token revalidate	Allow user to do basic authentication if a token expires or gets deregistered	
webdavSupport	Allow WebDAV	Activate WebDAV for files stored in solution records	

Single Sign On

System name	Display name	Explanation	Extra info
oauthLoginDisplay	SSO from login page	Display SSO links on login page	
oauthFacebookAllow	Facebook SSO active		
oauthFacebookClient	Facebook API username	https://developers.facebook.com/apps/	
oauthFacebookSecret	Facebook API password	https://developers.facebook.com/apps/	
oauthGoogleAllow	Google SSO active		
oauthGoogleClient	Google API username	https://developer.linkedin.com/documents/authentication	
oauthGoogleSecret	Google API password	https://developer.linkedin.com/documents/authentication	
oauthLinkedInAllow	LinkedIn SSO active		
oauthLinkedInClient	LinkedIn API username	https://console.developers.google.com/project/ts-oauth2-v1000/apiui/credential?clientType	
oauthLinkedInSecret	LinkedIn API password	https://console.developers.google.com/project/ts-oauth2-v1000/apiui/credential?clientType	