OLAP cubes

System name	Display name	Explanation	Extra info
olapDateDimensionYearEnd	OLAP Time dimension last year		
olapDateDimensionYearStart	OLAP Time dimension first year		
olapEngineFolderURL	OLAP engine URL (optional)		
olapRebuildOnBoot	Rebuild OLAP on boot	Rewrite cube definitions and queries	
olapUseSingleSignon	OLAP Single Sign On	Allow external users with security tokens (set OLAP folder to use dedicated server)	
allowRemoteOlapSchema	OLAP schema service	Activate schema delivery service (remote OLAP servers)	
olapSchemaPassword	OLAP schema service password	Experimental: Password for use with the schema delivery service (remote OLAP servers)	
olapJPivotEnabled	JPivot OLAP enabled	Is the internal OLAP engine enabled (JPivot)	
olapJpivotIncludeDefaultCubes	Jpivot schema include default cubes	Include autogenerated cubes with generated permissions	
olapSaikuEnabled	Saiku OLAP enabled	Experimental: Is the external OLAP engine enabled (saiku)	
olapSaikuIncludeCustomCubes	Saiku schema include custom cubes	Include custom cubes with default permissions	
olapSaikuSettingWebapp	Optional saiku web application name	Default if value is left empty: <current webapp name> + "Saiku"	Example: /SaikuWebapp
olapSaikuSettingServerUrl	Optional saiku server URL	Default if value is left empty: <same server>	Example: http://myserver.com

Revision #2
Created 7 April 2025 08:22:02 by Theis Villumsen
Updated 18 September 2025 13:43:58 by Max Gøtske