

Special functionality

- OLAP Activity
- OLAP Flowsteps
- OLAP Flow total
- OLAP fact builder
- Import from AD
- Sync Azure AD
- Kontoafstemning
- Satelite synchronize
- Satelite synch data
- Custom codeunit
- Data index builder
- File index builder
- Run BI SQL

OLAP Activity

Build data tables in standard OLAP cubes

[Describe the function the service executes]

Configuration

[If any configuration is available, and how to]

Developer info

- Classname: dk.p2e.blanket.services.BuildOlapActivity
- Default isActive:
- Default interval:

OLAP Flowsteps

Build data tables in standard OLAP cubes

[Describe the function the service executes]

Configuration

[If any configuration is available, and how to]

Developer info

- Classname: dk.p2e.blanket.services.BuildOlapFlowsteps
- Default isActive:
- Default interval:

OLAP Flow total

Build data tables in standard OLAP cubes

[Describe the function the service executes]

Configuration

[If any configuration is available, and how to]

Developer info

- Classname: dk.p2e.blanket.services.BuildOlapFlowtotal
- Default isActive:
- Default interval:

OLAP fact builder

Build data tables in standard OLAP cubes

[Describe the function the service executes]

Configuration

[If any configuration is available, and how to]

Developer info

- Classname: dk.p2e.blanket.services.BuildOlapGeneric
- Default isActive:
- Default interval:

Import from AD

Synchronize users/groups in LDAP repository

[Describe the function the service executes]

Configuration

[If any configuration is available, and how to]

Developer info

- Classname: dk.p2e.blanket.services.LDAPimport
- Default isActive:
- Default interval:

Sync Azure AD

Synchronize Azure groups and users

[Describe the function the service executes]

Configuration

[If any configuration is available, and how to]

Developer info

- Classname: dk.tempusserva.services.azureusers.DirectorySynchronizer
- Default isActive:
- Default interval:

Kontoafstemning

Bygger afstemninger til brug for kontoafstemning (se vejledning)

[Describe the function the service executes]

Configuration

[If any configuration is available, and how to]

Developer info

- Classname: `dk.p2e.blanket.solution.afstemning.KontoafstemningBuilder`
- Default `isActive`:
- Default interval:

Satelite synchronize

Keep a slave server model and data in sync

[Describe the function the service executes]

Configuration

[If any configuration is available, and how to]

Developer info

- Classname: dk.p2e.blanket.services.SateliteSynchronize
- Default isActive:
- Default interval:

Satelite synch data

[Describe the function the service executes]

Configuration

[If any configuration is available, and how to]

Developer info

- Classname: dk.p2e.blanket.services.SateliteSynchronizeData
- Default isActive:
- Default interval:

Custom codeunit

Run custom codeunit defined in policy

[Describe the function the service executes]

Configuration

[If any configuration is available, and how to]

Developer info

- Classname: dk.p2e.blanket.services.RunCustomCodeunit
- Default isActive:
- Default interval:

Data index builder

Transfer uncommitted data to search engine

[Describe the function the service executes]

Configuration

[If any configuration is available, and how to]

Developer info

- Classname: `dk.tempusserva.lucene.index.ServiceIndexDataStore`
- Default `isActive`:
- Default interval:

File index builder

Process files in queue

[Describe the function the service executes]

Configuration

[If any configuration is available, and how to]

Developer info

- Classname: `dk.tempusserva.lucene.index.ServiceIndexFileQueue`
- Default `isActive`:
- Default interval:

Run BI SQL

Runs sql for entities with config called biSqlQuery

[Describe the function the service executes]

Configuration

[If any configuration is available, and how to]

Developer info

- Classname: com.tsnocode.engine.services.BiService
- Default isActive:
- Default interval: