

WebDAV

About our WebDAV implementation

Supported document types: Word, Excel, Powerpoint.

The implementation does not require SSL to be enabled on the server, but it is recommended.



Sometimes the action of saving a file, that was opened using WebDAV will fail, but only the first time, if it happens at all.

To fix this, you just have to save the document again, and the issue will be gone for you, until you re-sign-in.

How to enable

Toggle the policy `webdavSupport` and `webdavSessionTokens` to `true`.

FIL

 HelloWorld.docx [7] 

 Beregningsark print.xlsx 

When WebDAV is enabled, the files-field, will add tiny pencils next to the supported file-types.

Clicking on the file icon will prompt the file to be opened in the associated application. Clicking on the filename, will prompt a download of the file.

You can control how long the auth-tokens are valid for, using policy `webdavSessionLifetime`.

You can control whether a token should automatically be re-validated if it times out using policy `webdavSessionTokensRevalidate`.

Testing WebDAV

Upload a word or excel file to a file field and save the record.

Re-open the record and click the type icon with the pencil next to the file name.

If the appropriate program opens, edit the file and save it.

Close the program.

Open the file again (either download it or re-open it via WebDAV), if your changes are still there, WebDAV is working.

Common config issues

The following policies have to be set up correctly, otherwise the WebDAV feature will not work.

applicationServer

applicationIsBehindAReverseProxy

applicationName

applicationBasePath

securitySslPages

Map WebDAV as a drive

Add a network location with the address `https://[domain]/[app]/webdav/drive/`.

On linux, replace the protocol with `davs`.

Enabling basic auth to your server

Office has stopped officially supporting Basic-auth, which is the backup authentication for our implementation.

To allow Office to connect to your server, and authenticate using Basic-auth, execute the following command, as admin, from the commandline.

```
REG ADD HKEY_CURRENT_USER\Software\Policies\Microsoft\Office\16.0\Common\Identity /t REG_EXPAND_SZ /v  
basichostallowlist /d "HOSTNAME"
```

Where HOSTNAME is the domain of your server, eg. `wiki.tsnocode.com`.

How to enable support in LibreOffice on Debian

Run the following commands

```
xdg-mime default libreoffice-writer.desktop x-scheme-handler/ms-word  
xdg-mime default libreoffice-calc.desktop x-scheme-handler/ms-excel  
xdg-mime default libreoffice-impress.desktop x-scheme-handler/ms-powerpoint
```

Revision #6

Created 8 April 2025 13:11:39 by Theis Villumsen

Updated 18 February 2026 10:55:55 by Theis Villumsen