

Form templates

Structure and syntax

The structure of the tags in the HTML template are

- {header}
- {tablename}
- {pageselector}
- {default_start}
 - {default_name}
 - {default_value}
 - {default_help}
- {default_end}
- {defaultField}
- {footer}

You may also add additional tags for special fields:

- "{ + [field systemname] + "_name}"
- "{ + [field systemname] + "_value}"
- "{ + [field systemname] + "_help}"

Template handling

Templates are injected with values from the current record like this

1. For each field
 1. Try to inject [system fieldname] + [prefix]
 2. If failed
 - Copy content from {default_start} to {default_end}
 - Inject values into content copy
 - Inject content copy into {defaultField}
2. Inject the form page selector into {pageselector}
 1. If failed: Ignore

Missing values for default_XXX tags will automatically get appended to the template.

Relation til styling

type	class	id	content	template
tbody	PAGE_[field PageID]		Container for a single field	{default_start} / {default_end}
div	FieldLabel	NB_[system fieldname]	Label for field	{default_name}
div	FieldValue	VB_[system fieldname]	Value of field / Input for field	{default_value}
div	FieldNotes	HB_[system fieldname]	Optional help text for the field	{default_help}

Example

```
{header}

<h3>{tablename}</h3>

<table class='tableForm'>
  <tr><td style="padding: 0px; border: 0px;">{pageselector}</td></tr>
  {default_start}
  <tr>
    <td class="tableFieldTableLabel"><p>{default_name}</p></td>
  </tr>
  <tr>
    <td class="tableFieldTableValue">
      <p>{default_value}</p>
      <p>{default_help}</p>
    </td>
  </tr>
  {default_end}
  {defaultField}
</table>

{footer}
```

Revision #1

Created 4 April 2025 10:43:26 by Theis Villumsen

Updated 4 April 2025 10:44:14 by Theis Villumsen